



# **SWSI**

**Southern Welding Systems International LLC**

**Welding | Industrial | Safety**

**International Wholesale Distribution**

**Contact us for Pricing:**

**Phone: 281-485-9772 | Fax: 281-485-4386**

**Email: [Sales@swsintl.com](mailto:Sales@swsintl.com) | Website: [www.swsintl.com](http://www.swsintl.com)**

**Address: 3908 1st Street Pearland, Texas 77581**

# INDUSTRIAL & MRO CHEMICALS

## A Leader in Chemical Product Solutions

LA-CO Industries, Inc. has been making quality plumbing and chemical products for the past seven decades. From Slic-tite® and LA-CO® Regular Flux for the professional plumber, to EZ Break® for the industrial chemical processing plant, LA-CO manufactures products to fit the needs of today's industry. For a full list of available products please refer to our Plumbing & Chemical Products Catalog, or visit our web site at [www.laco.com](http://www.laco.com).

### SLIC-TITE® PASTE WITH PTFE

### Premium Thread Sealant

- Contains more PTFE particles for greater sealing power
- Use on metal, PVC, CPVC and ABS plastic pipe threads
- For sealing water, air, steam, natural gas, LP gas, refrigerants, ammonia, gasoline, ethanol and oil
- Low V.O.C.'s
- Do not use on oxygen service; use Slic-Tite® PTFE Thread Tape or Oxytite® Paste
- Washes off hands and clothing easily
- Non-toxic, non-drying
- Sealing temperature range: -50°F to 500°F (-46°C to 260°C)

- Working pressures: 3,000 PSI (204 BAR) for gas, 10,000 PSI (680 BAR) for liquids
- USDA approved for use in federally inspected meat and poultry plants
- **New** – Noveon approved
- Made in the U.S.A.



PART NO.	SIZE	CASE QTY.
41209	1/4 pt. BIC	12
42009	1/4 pt. BIC	24
41219	1/2 pt. BIC	12
42019	1/2 pt. BIC	24
42012	1 pt.	24
42029	1 pt. BIC	24
42013	1 qt.	12
42049	1 qt. BIC	12
42014	1 gal.	4
42015	5 gal.	1
42069	55 gal.	1
<b>Dozen Display Pack Tubes</b>		
42002	1-1/2 oz.	24
BIC = Brush in Cap		



### LEAK-TITE® BLUE

### Economical Thread Sealant with PTFE



- Contains PTFE particles for greater sealing power
- Will not harden or dry out over time; remains flexible for easy disassembly
- Non-toxic, contains no solvents
- Sticks to hot, oily threads
- Ideal for use on production lines and fabrication shops
- Easy clean-up, will not stain hands or clothing
- For use on metal and PVC plastic pipe threads
- For sealing water, air, steam, natural gas, refrigerants, gasoline and ammonia
- Do not use on oxygen service; use Slic-Tite® PTFE thread tape or Oxytite® paste
- Sealing temperature: -50°F to 500°F (-45°C to 260°C)
- Pressures: to 1,500 PSI (102 BAR) for gas, to 5,000 PSI (340 BAR) for liquid
- Low V.O.C.'s
- Made in the U.S.A.



PART NO.	SIZE	CASE QTY.
46029	1 pt. BIC	24
46013	1 qt.	12
46049	1 qt. BIC	12
46014	1 gal.	4
46015	5 gal.	1
46069	55 gal.	1

BIC = Brush in Cap



### REGULAR FLUX PASTE

### Cleans As It Solders

- Super detergent action cleans as it solders
- Water soluble for faster rinsing from pipe lines
- Contains no zinc chloride
- Use with all lead-free and common soft solders
- For use on copper; brass, galvanized iron, lead, zinc, tin, silver; nickel, mild steel, terne plate and malleable iron
- Meets Mil. Spec. Mil-F-4995 Type II
- Meets ASTM B813
- All weather
- Made in the U.S.A.



PART NO.	SIZE	CASE QTY.
22101	2 oz.	48
22104	4 oz.	48
22194	4 oz. BIC	48
22107	1 lb.	24

BIC = Brush in Cap





# INDUSTRIAL & MRO CHEMICALS

## COOL GEL®

### Heat Barrier Spray



SEE COOL GEL IN ACTION AT [www.coolgelmovie.com](http://www.coolgelmovie.com)



- Helps prevent heat damage to components and surrounding materials during soldering, brazing and welding
- Protects painted and finished surfaces from discoloration due to adjacent torch operations
- Unique gelled formula sticks to surfaces without dripping or running off
- Clear, non-staining gel leaves no residue, eliminating clean-up

- Safe, non-toxic, harmless to skin and odorless
- Reduces danger of fire to surrounding surfaces such as rubber and plastic seals and gaskets
- Convenient trigger spray
- Made in the U.S.A.



PART NO.	SIZE	CASE QTY.
11513	16 oz.	24
11509	32 oz.	12
<b>Display Box</b>		
11524	2 oz.	48



Cool Gel protects surfaces when welding

## EPOXY-STIK® ANTI-SEIZE COMPOUND

### Epoxy Repair Compound



- Cures rock-hard with no shrinkage
- Safe on potable water systems
- Withstands temperatures up to 250°F (120°C)
- Hardens in 5-10 minutes, full cure in 24 hours
- Can be applied under water
- After 1 hour can be drilled, tapped, filed, sawed, sanded and painted
- Made in the U.S.A.



PART NO.	SIZE	CASE QTY.
<b>Dozen Display Box</b>		
19571	4 oz.	24



## EZ BREAK® ANTI-SEIZE COMPOUND

### Copper Grade



- Copper-based anti-seize and lubricating compound
- Recommended for coating nuts, bolts, valves, flanges, splines for easy break out after years of service
- Resists rust and corrosion
- Meets Mil. Spec. Mil-A-907E

- Authorized by USDA for use in federally inspected meat and poultry plants
- Temperature: to 1800°F (982°C)
- Made in the U.S.A.



PART NO.	SIZE	CASE QTY.
08924	4 oz. BIC	24
08910	10 oz. BIC	24
08916	14 oz. Aerosol	12
08907	16 oz. BIC	24
08925	8 lbs.	4
08950	42 lbs.	1
08969	425 lbs.	1

BIC = Brush in Cap

## EZ BREAK® ANTI-SEIZE COMPOUND

### Nickel Grade



- Contains fine particles of nickel and other additives
- Contains no copper
- Resists rust and corrosion
- Makes disassembly easy, even after years of service

- Helps prevent galling of stainless steel threads
- Temperature: to 2600°F (1427°C)
- Made in the U.S.A.



PART NO.	SIZE	CASE QTY.
08971	8 oz. BIC	24
08972	16 oz. BIC	24
08973	8 lbs.	4
08978	42 lbs.	1
08979	425 lbs.	1

BIC = Brush in Cap

# INDUSTRIAL & MRO CHEMICALS

## PIERCE™

### Rust Remover, Penetrant and Lubricant



- Drives under rust and penetrates into the tightest crevices to protect against rust and corrosion
- Removes asphalt, tar, grease, dirt from metal surfaces
- Colorless, moisture-repellent film guards against continuing rust and corrosion
- Use on all equipment, tools, chainsaws, cables, ignition systems, treaded parts, and any rotating or sliding metal surfaces
- Lubricates and eliminates squeaks
- Displaces moisture
- Made in the U.S.A.



PART NO.	SIZE	CASE QTY.
79711	12 oz.	24

## RUST BUSTER®

### Rust Penetrant



- Goes to work instantly, every time
- Packaged in handy, telescoping spout applicator
- Quickly loosens rusted bolts, screws, shafts, piping, all types of "frozen" connections and assemblies
- Contains no acids, alkali or other harmful ingredients
- Safe for all skin, clothes, metals and friction-type surfaces
- The penetrant used by professional mechanics in industry and the military
- Flexible telescoping-spout extends 7" for difficult-to-reach areas
- Made in the U.S.A.



PART NO.	SIZE	CASE QTY.
<b>Dozen Display Box</b>		
79706	4 fl. oz.	24

## ZOOM SPOUT® OILER

### Lubricating Oil for General Applications



- Premium-grade, all-purpose, turbine-grade lubricating oil for general applications
- Use on rotating and reciprocating equipment, bearings, motors and slides
- Flexible telescoping-spout extends 7" for difficult-to-reach areas
- Made in the U.S.A.



PART NO.	SIZE	CASE QTY.
<b>Dozen Display Box</b>		
79704	4 fl. oz.	24

## SLIC-TITE® PTFE THREAD TAPE High-Density, Premium-Grade



- Thickness 4 mils
- High-density
- Provides a highly resistant seal on pipe threads for all types of service
- Suitable for use with solvents, chemicals, oxygen and on food lines
- Non-toxic
- Permits easy disassembly, even after many years
- Meets Mil. Spec. T-27730A
- Sealing temperature range: -450°F to 550°F (-268°C to 288°C)
- Pressure: to 2,000 PSI (136 BAR)
- NEW Yellow for gas line and Pink for water line usage



PART NO.	SIZE	CASE QTY.
<b>Dozen Display Box</b>		
44080	1/4" x 300"	12
44081	1/4" x 600"	12
44082	1/2" x 300"	12
44083	1/2" x 600"	12
44084	1/2" x 1200"	12
44085	3/4" x 300"	12
44086	3/4" x 600"	12
44087	1" x 300"	12
44088	1" x 600"	12
44094	1/2" x 260" Yellow	12
44095	1/2" x 260" Pink	12
<b>Carded - 2 per Card</b>		
44003	1/2" x 600"	12

## PTFE THREAD TAPE

### Contractor-Grade



- Thickness 3 mils
- Contractor-grade, low-density
- Provides a highly resistant seal on pipe threads for all types of service
- Suitable for use with solvents, chemicals, oxygen and on food lines
- Non-toxic
- Permits easy disassembly, even after years of service
- Meets Mil. Spec. T-27730A
- Sealing temperature range: -450°F to 550°F (-268°C to 288°C)
- Pressure: to 2,000 PSI (136 BAR)



PART NO.	SIZE	CASE QTY.
44070	1/4" x 520"	144
44071	1/2" x 260"	144
44072	1/2" x 520"	144
47272	1/2" x 520"	72
44073	1/2" x 1296"	144
44074	3/4" x 260"	144
44075	3/4" x 520"	144
44076	3/4" x 1296"	144
44077	1" x 260"	144
44078	1" x 520"	144
44079	1" x 1296"	144